

Kategorija: **Intel matične ploče**

Proizvođač: **Gigabyte**

Matična ploča 1851 Gigabyte Z890 AORUS ELITE WIFI7 ICE

Šifra: **4719331865269**

Matična ploča 1851 Gigabyte Z890 AORUS ELITE WIFI7 ICE

Maloprodajna cena: 39.990,00 RSD

Web cena: 38.990,00 RSD

Ušteda: 1.000,00 RSD

Specifikacija

Model	Gigabyte Z890M AORUS ELITE WIFI7 ICE DDR5 Micro ATX LGA1851 Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1851
Skup čipova (Chipset)	Intel Z890M
Podrška za procesore	Support for Intel Core Ultra Processors L3 cache varies with CPU
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5

Podrška za memorije

Support for DDR5
9200(O.C) / 9066(O.C) /
8933(O.C) / 8800(O.C) /
8600(O.C) / 8400(O.C)
/8266(O.C) / 8200(O.C)
/ 8000(O.C) / 7950(O.C)
/ 7900(O.C) / 7800(O.C)
/ 7600(O.C.) /
7400(O.C.) / 7200(O.C.)
/ 7000(O.C.) /
6800(O.C.) / 6600(O.C.)
/ 6400 / 6200 / 6000 /
5800 / 5600MT/s
memory modules.
Support for DDR5
6400/5600 MT/s
memory modules
4 x DDR5 DIMM sockets
supporting up to 256
GB (64 GB single DIMM
capacity) of system
memory
Dual channel memory
architecture
Support for ECC Un-
buffered DIMM
1Rx8/2Rx8 memory
modules (operate in
non-ECC mode)
Support for non-ECC Un-
buffered DIMM
1Rx8/2Rx8/1Rx16
memory modules
Support for Extreme
Memory Profile (XMP)
memory modules
Support CUDIMM
memory module

Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support: - 1 x USB4 USB Type-C port, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 144Hz Support for DisplayPort 2.1 version - 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144Hz Support for DisplayPort 2.1 version - 1 x front HDMI port, supporting a maximum resolution of 1920x1080 30Hz Support for HDMI 1.4 version
Slotovi za proširenja	CPU: - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16) The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)
M.2 portovi	3x M.2 Socket 3

Čuvanje podataka - portovi	CPU: - 1 x M.2 connector (Socket 3, M key, type 2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A_CPU) - 1 x M.2 connector (Socket 3, M key, type 2580/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU) Chipset: - 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD support) (M2Q_SB) - 4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	MediaTek Wi-Fi 7 MT7925 (PCB rev. 1.0) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard Realtek Wi-Fi 7 RTL8922AE (PCB rev. 1.1) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard
Bluetooth	5.4
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel Support for S/PDIF Out

USB portovi	CPU: - 1 x USB4 USB Type-C port on the back panel Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header - 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel - 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) Chipset+2 USB 2.0 Hubs: - 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x USB4 USB Type-C port (DisplayPort(Note)) 1 x USB 3.2 Gen 2 Type-A port (red) 4 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 2 x antenna connectors (2T2R) 1 x DisplayPort (Note) 1 x RJ-45 port 1 x optical S/PDIF Out connector 2 x audio jacks Actual support may vary by CPU.

Unutrašnji konektori	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header 1 x CPU fan/water cooling pump header 3 x system fan headers 1 x system fan/water cooling pump header 3 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 3 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt™ add-in card connectors 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x HDMI port 1 x power button 1 x reset button 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup
Operativni sistem	Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Format	Micro ATX
Prava potrošača:	Zakonska saobraznost 2 godine
EAN:	4719331865269

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.