

Kategorija: **AMD matične ploče**
Proizvođač: **Asus**

Šifra: **4711387718148**
Matična ploča ASUS PRIME X870-P

Matična ploča ASUS PRIME X870-P

Maloprodajna cena: 42.990,00 RSD

Web cena: 41.990,00 RSD

Ušteda: 1.000,00 RSD

Specifikacija

Model	Asus PRIME X870-P WIFI DDR5 AM5 ATX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD X870
Podrška za procesore	AMD Socket AM5 for AMD Ryzen 9000 & 8000 & 7000 Series Desktop Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
Podrška za memorije	4 x DIMM slots, max. 192GB, DDR5 Supports up to 8000+MT/s(OC) with Ryzen 9000 & 8000 & 7000 Series Desktop Processors ECC and Non-ECC, Un-buffered DIMM Dual channel memory architecture Supports AMD Extended Profiles for Overclocking (EXPO) ASUS Enhanced Memory Profile (AEMP) Adjustments will be made based on the specifications of mass-produced memory modules available on the market.
Podrška za grafiku - portovi	1 x HDMI port 2 x USB4 (40Gbps) ports support USB Type-C display outputs Graphics specifications may vary between CPU types. Please refer to the specifications of the CPU. Supports 4K 60Hz as specified in HDMI 2.1. Supports max. 4K 60Hz as specified in DisplayPort 1.4a. VGA resolution support depends on processors' or graphic cards' specifications.
Slotovi za proširenja	AMD Ryzen 9000 & 7000 Series Desktop Processors 1 x PCIe 5.0 x16 slot (supports x16 mode) AMD Ryzen 8000 Series Desktop Processors 1 x PCIe 4.0 x16 slot (supports x8/x4 mode) AMD X870 Chipset 3 x PCIe 4.0 x16 slots (support x1 mode)
M.2 portovi	4x M.2 Socket 3

Čuvanje podataka - portovi	Supports 4 x M.2 slots and 2 x SATA 6Gb/s ports AMD Ryzen 9000 & 7000 Series Desktop Processors M.2_1 slot (Key M), type 2280 (supports PCIe 5.0 x4 mode) AMD Ryzen 8000 Series Desktop Processors M.2_1 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) AMD X870 Chipset M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) M.2_3 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) M.2_4 slot (Key M), type 2280 (supports PCIe 3.0 x2 mode) 2 x SATA 6Gb/s ports PCIEX16(G4)_1 shares bandwidth with M.2_2. PCIEX16(G4)_1 will be disabled when M.2_3 runs. M.2_4 shares bandwidth with SATA6G_1 and SATA6G_2. M.2_4 will be disabled when SATA6G_2 runs. AMD RAIDXpert2 Technology Ryzen 9000 Series Processors: RAID 0/1/5/10 Ryzen 8000 Series Processors: RAID 0/1 Ryzen 7000 Series Processors: RAID 0/1/10 Supports 4 x M.2 slots and 2 x SATA 6Gb/s ports AMD Ryzen 9000 & 7000 Series Desktop Processors M.2_1 slot (Key M), type 2280 (supports PCIe 5.0 x4 mode) AMD Ryzen 8000 Series Desktop Processors M.2_1 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) AMD X870 Chipset M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) M.2_3 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) M.2_4 slot (Key M), type 2280 (supports PCIe 3.0 x2 mode) 2 x SATA 6Gb/s ports PCIEX16(G4)_1 shares bandwidth with M.2_2. PCIEX16(G4)_1 will be disabled when M.2_3 runs. M.2_4 shares bandwidth with SATA6G_1 and SATA6G_2. M.2_4 will be disabled when SATA6G_2 runs. AMD RAIDXpert2 Technology Ryzen 9000 Series Processors: RAID 0/1/5/10 Ryzen 8000 Series Processors: RAID 0/1 Ryzen 7000 Series Processor
	SATA portovi
	LAN
	Bežična mreža
	Bluetooth
	Zvuk (Audio)

USB portovi	Rear USB (Total 10 ports) 2 x USB4 (40Gbps) ports (2 x USB Type-C) 1 x USB 10Gbps port (1 x Type-A) 3 x USB 5Gbps ports (3 x Type-A) 4 x USB 2.0 ports (4 x Type-A) Front USB (Total 7 ports) 1 x USB 10Gbps connector (supports USB Type-C) 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports 2 x USB 2.0 headers support 4 additional USB 2.0 ports USB Type-C power delivery output: max. 5V/3A
Konektori na zadnjoj strani	2 x USB4 (40Gbps) ports (2 x USB Type-C) 1 x USB 10Gbps port (1 x Type-A) 3 x USB 5Gbps ports (3 x Type-A) 4 x USB 2.0 ports (4 x Type-A) 1 x HDMI port 1 x Wi-Fi module 1 x Realtek 2.5Gb Ethernet port 3 x Audio jacks 1 x BIOS FlashBack button
Unutrašnji konektori	Fan and Cooling Related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 1 x 4-pin AIO Pump header 4 x 4-pin Chassis Fan headers Power Related 1 x 24-pin Main Power connector 2 x 8-pin +12V CPU Power connectors Storage Related 4 x M.2 slots (Key M) 2 x SATA 6Gb/s ports USB 1 x USB 10Gbps connector (supports USB Type-C) 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports 2 x USB 2.0 headers support 4 additional USB 2.0 ports Miscellaneous 3 x Addressable Gen 2 headers 1 x Clear CMOS header 1 x COM Port header 1 x Front Panel Audio header (F_AUDIO) 1 x S/PDIF Out header 1 x SPI TPM header (14-1 pin) 1 x 10-1 pin System Panel header

Posebne mogućnosti	ASUS 5X PROTECTION III - DIGI+ VRM (- Digital power design with DrMOS) - LANGuard - Overvoltage protection - SafeSlot - Stainless-steel back I/O ASUS Q-Design - M.2 Q-Latch - PCIe Slot Q-Release - Q-Antenna - Q-Dashboard - Q-DIMM - Q-LED Core - Q-Slot ASUS Thermal Solution - Flexible M.2 heatsink - VRM heatsink design ASUS EZ DIY - BIOS FlashBack button - BIOS FlashBack LED - ProCool - Pre-mounted I/O shield - SafeSlot Aura Sync - Addressable Gen 2 headers ASUS Exclusive Software Armoury Crate - Aura Creator - Aura Sync - Fan Xpert 4 (with AI Cooling II) - Power Saving ASUS DriverHub ASUS GlideX TurboV Core ASUS CPU-Z Norton 360 Deluxe (60 Days Free Trial) WinRAR (40 Days Free Trial) UEFI BIOS ASUS EZ DIY - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode - ASUS MyHotkey
	Operativni sistem
	BIOS
	Format
	Dodatna oprema

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.