

Kategorija: **Intel matične ploče**


Proizvođač: **Gigabyte**

**Maticna ploca 1700 Gigabyte B760M D3HP
WIFI6 DDR5 VGA/HDMI/DP/M.2**

Maloprodajna cena: 14.990,00 RSD

Web cena: 14.990,00 RSD

Šifra: **4719331867638**



Specifikacija

CPU	LGA1700 socket: Supports 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold, and Celeron® Processors (Check GIGABYTE's website for the latest CPU support list.) L3 cache varies with CPU
Chipset	Intel® B760 Express Chipset
Memory	14th & 13th Gen Intel® Core™ i9/i7: DDR5 5600/5200/4800/4400 MT/s; 13th Gen Intel® Core™ i5/i3 & 12th Gen Intel® Core™, Pentium® Gold, and Celeron®: DDR5 4800/4400 MT/s 4 x DDR5 DIMM sockets, up to 192 GB (48 GB per DIMM) Dual channel memory architecture Supports ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (non-ECC mode) Supports non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Supports Extreme Memory Profile (XMP)
Onboard Graphics	Intel® HD Graphics support 1 x D-Sub (1920x1200@60Hz max), 1 x HDMI (4096x2160@60Hz max) with HDMI 2.1 and HDCP 2.3 1 x DisplayPort (4096x2304@60Hz max), DisplayPort 1.2 and HDCP 2.3 Supports up to triple-display
Audio	Realtek® Audio CODEC, High Definition Audio, 2/4/5.1/7.1-channel Supports S/PDIF Out
LAN	Realtek® GbE LAN chip (1 Gbps/100 Mbps/10 Mbps)
Wireless Communication	Realtek® Wi-Fi 6 RTL8851BE: WIFI a/b/g/n/ac/ax, 2.4/5 GHz frequency, Bluetooth 5.3 Supports 11ax 80MHz wireless standard
Expansion Slots	1 x PCIe x16 (PCIe 4.0, x16) for graphics or NVMe SSD 2 x PCIe x1 (PCIe 3.0, x1)
Storage Interface	1 x M.2 (Socket 3, M Key, 2280 PCIe 4.0 x4/x2 SSD) 1 x M.2 (Socket 3, M Key, 2280 PCIe 4.0 x4/x2 SSD) 4 x SATA 6Gb/s RAID 0, RAID 1, RAID 5, RAID 10 support

USB	<ul style="list-style-type: none"> 1 x USB Type-C® (USB 3.2 Gen 1, internal) 5 x USB 3.2 Gen 1 (3 on the back panel, 2 internal) 2 x USB 2.0/1.1 ports (back panel) 4 x USB 2.0/1.1 ports (internal)
Internal I/O Connectors	<ul style="list-style-type: none"> 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 3 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 2 x M.2 connectors, 4 x SATA 6Gb/s 1 x front panel header 1 x USB Type-C® header (USB 3.2 Gen 1) 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module (TPM) header 1 x serial port header 1 x parallel port header 1 x S/PDIF Out header 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Back Panel Connectors	<ul style="list-style-type: none"> 2 x USB 2.0/1.1 ports 1 x PS/2 keyboard/mouse port 2 x SMA antenna connectors 1 x D-Sub port 1 x DisplayPort 1 x HDMI port 3 x USB 3.2 Gen 1 ports 1 x RJ-45 port 3 x audio jacks
I/O Controller	iTE® I/O Controller Chip
H/W Monitoring	Voltage, Temperature, Fan speed detection, Water cooling flow rate detection, Fan fail warning, Fan speed control (dependent on installed fan)
BIOS	128 Mbit flash, AMI UEFI BIOS
Unique Features	GIGABYTE Control Center (GCC) Support, Q-Flash, Q-Flash Plus
Bundled Software	Norton® Internet Security (OEM), LAN bandwidth management
Operating System	Windows 11 64-bit, Windows 10 64-bit
Form Factor	Micro ATX (24.4 cm x 24.4 cm)

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.