

Kategorija: **AMD matične ploče**

Proizvođač: **Gigabyte**

Matična ploča Gigabyte AM5 X870I AORUS PRO ICE

Web cena: 42.990,00 RSD

Šifra: **X870I AORUS PRO ICE**



Specifikacija

Model	Gigabyte X870I AORUS PRO ICE AM5 DDR5 Mini-ITX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD X870I
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	2x 288-Pin DDR5 Support for DDR5 8400(OC) / 8200(OC) / 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s memory modules 2 x DDR5 DIMM sockets supporting up to 128 GB (64 GB single DIMM capacity) of system memory
Podrška za memorije	Dual channel memory architecture Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for AMD Extended Profiles for Overclocking (AMD EXPO) and Extreme Memory Profile (XMP) memory modules (The CPU and memory configuration may affect the supported memory types, data rate (speed), and number of DRAM modules, please refer to "Memory Support List" on GIGABYTE's website for more information.)

	Integrated Graphics Processor with AMD Radeon Graphics support+ASMedia USB4 Controller: - 1 x USB4 USB Type-C port, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 240Hz Support for DisplayPort 1.4 version and HDR.
Podrška za grafiku - portovi	Integrated Graphics Processor with AMD Radeon Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version and HDCP 2.3, and HDR. Support for native HDMI 2.1 TMDS compatible ports.
	(Graphics specifications may vary depending on CPU support.)
Slotovi za proširenja	1 x PCI Express x16 slot, integrated in the CPU: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 mode AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode The PCIe x16 slot can only support a graphics card or an NVMe SSD.
M.2 portovi	3x M.2 Socket 3 1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 2280 SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs
Čuvanje podataka - portovi	1 x M.2 connector on the back of the motherboard (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSDs 2 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices RAID 5 is only available on AMD Ryzen 9000 Series Processors.
	RAID 0 and RAID 1 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Realtek Wi-Fi 7 RTL8922AE - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - BLUETOOTH 5.4 - Support for 11be 160MHz wireless standard (Actual data rate may vary depending on environment and equipment.)
Bluetooth	BLUETOOTH 5.4
Zvuk (Audio)	Realtek ALC4080 CODEC High Definition Audio 2-channel
	CPU+ASMedia USB4 controller: - 1 x USB4 USB Type-C port on the back panel
USB portovi	CPU: - 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2 support - 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header - 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) - 4 x USB 2.0/1.1 ports (2 ports on the back panel, 2 ports available through the internal USB header)

Konektori na zadnjoj strani	1 x Q-Flash Plus button
	1 x HDMI port (Note)
	2 x antenna connectors (2T2R)
	1 x USB4 USB Type-C port (DisplayPort (Note))
	1 x USB Type-C port, with USB 3.2 Gen 2 support
	2 x USB 3.2 Gen 2 Type-A ports (red)
	2 x USB 3.2 Gen 1 ports
	2 x USB 2.0/1.1 ports
	1 x RJ-45 port
	2 x audio jacks
Unutrašnji konektori	(Note) Actual support may vary by CPU.
	1 x 24-pin ATX main power connector
	1 x 8-pin ATX 12V power connector
	1 x CPU fan header
	1 x CPU fan/water cooling pump header
	1 x system fan header
	2 x addressable RGB Gen2 LED strip headers
	1 x RGB LED strip header
	2 x M.2 Socket 3 connectors
	2 x SATA 6Gb/s connectors
	1 x front panel header
	1 x speaker header
	1 x front panel audio header (routed from the adapter card on the rear panel)
	1 x USB Type-C header, with USB 3.2 Gen 2 support
	1 x USB 3.2 Gen 1 header
	1 x USB 2.0/1.1 header
	1 x reset jumper
	1 x Clear CMOS jumper
	1 x chassis intrusion header
	Support for GIGABYTE Control Center (GCC)
Posebne mogućnosti	Support for Q-Flash
	Support for Q-Flash Plus
	Support for Smart Backup
	Voltage detection
	Temperature detection
	Fan speed detection
Operativni sistem	Water cooling flow rate detection
	Fan fail warning
	Fan speed control
	Windows 11
BIOS	1 x 256 Mbit flash
	Use of licensed AMI UEFI BIOS
	PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Mini-ITX

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.