

Kategorija: **Intel matične ploče**

Proizvođač: **Gigabyte**

**Matična ploča 1700 Gigabyte B760M
GAMING X DDR4 Gen5**

Maloprodajna cena: 16.990,00 RSD

Web cena: 16.990,00 RSD

Šifra: **4719331874087**



Specifikacija

Model	Gigabyte B760M GAMING X DDR4 GEN5 LGA1700 ATX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel B760
Podrška za procesore	Podrška za 14th, 13th, i 12th Generation Intel Core, Pentium Gold i Celeron Processors
Tip memorije (RAM)	DDR4
Broj memorijskih slotova	4x 288-Pin DDR4 Podržani DDR4 moduli brzine 5333(O.C.) / 5133(O.C.) / 5000(O.C.) / 4933(O.C.) / 4800(O.C.) / 4700(O.C.) / 4600(O.C.) / 4500(O.C.) / 4400(O.C.) / 4300(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 3000 / 2933 / 2666 / 2400 / 2133 MT/s4 x DDR4 DIMM slota sa podrškom za do 128 GB systemske memorije (do 32 GB po jednom DIMM modulu)Dvokanalna (dual-channel) arhitektura memorijePodrška za ECC un-buffered DIMM memorijske module tipa 1Rx8 / 2Rx8 (rade u non-ECC režimu)Podrška za non-ECC un-buffered DIMM memorijske module tipa 1Rx8 / 2Rx8 / 1Rx16Podrška za memorijske module sa Extreme Memory Profile (XMP) profilom(Konfiguracija procesora i memorije može uticati na podržane tipove memorije, brzinu prenosa podataka (brzinu) i broj DRAM modula. Za više informacija pogledajte „Memory Support List“ na sajtu kompanije GIGABYTE.)
Podrška za memorije	
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
Slotovi za proširenja	CPU: - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset: - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4)
M.2 portovi	2x M.2 Socket 3

Čuvanje podataka - portovi

SATA portovi

LAN

Zvuk (Audio)

USB portovi

Konektori na zadnjoj strani

Unutrašnji konektori

Posebne mogućnosti

Operativni sistem

BIOS

Format

Link ka proizvođaču

CPU:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU)**Chipset:-** 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices

4x SATA 6Gb/s

Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channelSupport for S/PDIF Out

Chipset:- 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header- 5 x USB 3.2 Gen 1 ports (3 ports on the back panel, 2 ports available through the internal USB header)- 1 x USB 2.0/1.1 port on the back panel**Chipset+2 USB 2.0 Hubs:-** 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)

3 x USB 3.2 Gen 1 ports5 x USB 2.0/1.1 ports2 x antenna connectors (2T2R)1 x HDMI port (Note)1 x DisplayPort (Note)1 x RJ-45 port3 x audio jacks

1 x 24-pin ATX main power connector1 x 8-pin ATX 12V power connector1 x CPU fan header3 x system fan headers3 x addressable LED strip headers1 x RGB LED strip header2 x M.2 Socket 3 connectors4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x S/PDIF Out header1 x USB Type-C header, with USB 3.2 Gen 2 support1 x USB 3.2 Gen 1 header2 x USB 2.0/1.1 headers2 x Thunderbolt add-in card connectors1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)1 x serial port header1 x Q-Flash Plus button1 x reset jumper1 x Clear CMOS jumper

Support for GIGABYTE Control Center (GCC)Support for Q-FlashSupport for Q-Flash PlusSupport for Smart BackupVoltage detectionTemperature detectionFan speed detectionWater cooling flow rate detectionFan fail warningFan speed control

Windows 10; Windows 11

1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Micro ATX

<https://www.gigabyte.com/>

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve

informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.