

Kategorija: **Intel matične ploče**Proizvođač: **Gigabyte****Matična ploča 1851 Gigabyte B860 DS3H
WIFI6E 1.0****Maloprodajna cena: 24.990,00 RSD****Web cena: 22.990,00 RSD****Ušteda: 2.000,00 RSD**Šifra: **B860 DS3H WIFI6E**

Specifikacija

Model	Gigabyte B860 DS3H WIFI6E LGA1851 DDR5 ATX Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1851
Skup čipova (Chipset)	Intel B860
Podrška za procesore	Intel Core Ultra Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5 Support for DDR5 9066(O.C)/8800(O.C) /8600(O.C) / 8400(O.C) /8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 5600 MT/s memory modules4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Podrška za memorije	Integrated Graphics Processor-Intel® HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144Hz
Podrška za grafiku - portovi	CPU:- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset:- 4 x PCI Express x16 slots, supporting PCIe 4.0 and running at x1 (PCIEX1_1~PCIEX1_4)
Slotovi za proširenja	2x M.2 Socket 3 CPU:- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A_CPU) Chipset:- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
M.2 portovi	4x SATA 6Gb/s
Čuvanje podataka - portovi	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
SATA portovi	
LAN	

Bežična mreža

Intel Wi-Fi 6E AX211 (PCB rev. 1.0)- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands- BLUETOOTH 5.3- Support for 11ax 160MHz wireless standard
Realtek Wi-Fi 6E RTL8852CE (PCB rev. 1.1)- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands- BLUETOOTH 5.3- Support for 11ax 160MHz wireless standard

Bluetooth

5.3

Zvuk (Audio)

Realtek Audio CODEC
High Definition Audio 2/4/5.1/7.1-channel
You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.
Support for S/PDIF Out

USB portovi

Chipset: 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2x2 support- 1 x USB Type-C port with USB 3.2 Gen 1 support, available through the internal USB header- 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel- 2 x USB 3.2 Gen 1 ports available through the internal USB header- 4 x USB 2.0/1.1 ports on the back panel
Chipset+USB 2.0 Hub: 4 x USB 2.0/1.1 ports available through the internal USB headers

Konektori na zadnjoj strani

1 x PS/2 keyboard/mouse port
1 x HDMI port
1 x DisplayPort
1 x USB Type-C port, with USB 3.2 Gen 2x2 support
1 x USB 3.2 Gen 2 Type-A port (red)
4 x USB 2.0/1.1 ports
1 x RJ-45 port
2 x antenna connectors (2T2R)
3 x audio jacks

Unutrašnji konektori

1 x 24-pin ATX main power connector
1 x 8-pin ATX 12V power connector
1 x CPU fan header
1 x CPU fan/water cooling pump header
2 x system fan headers
2 x system fan/water cooling pump headers
3 x addressable RGB Gen2 LED strip headers
1 x RGB LED strip header
2 x M.2 Socket 3 connectors
4 x SATA 6Gb/s connectors
1 x front panel header
1 x front panel audio header
1 x S/PDIF Out header
1 x USB Type-C header, with USB 3.2 Gen 1 support
1 x USB 3.2 Gen 1 header
2 x USB 2.0/1.1 headers
1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)
1 x serial port header
1 x Q-Flash Plus button
1 x reset jumper
1 x Clear CMOS jumper

Posebne mogućnosti

Support for GIGABYTE Control Center (GCC)
Support for Q-Flash
Support for Q-Flash Plus
Support for Smart Backup
Voltage detection
Temperature detection
Fan speed detection
Water cooling flow rate detection
Fan fail warning
Fan speed control

Operativni sistem

Windows 10; Windows 11

BIOS

1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Format

ATX

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.