

Kategorija: **SVIČEVI**

Proizvođač: **cudy**

Šifra: **GS1020PS2**

**Svič 10/100/1000 16-port Cudy GS1020PS2
PoE+ sa 2x SFP porta 200W**

Web cena: 17.990,00 RSD



Specifikacija

Model Version	GS1020PS2 3.0
1.25G SFP Slots	2
Gigabit RJ45 Ports	16
Gigabit RJ45 PoE Ports	#1~#16
Max Power on a Single PoE Port	30W
PoE Port Notes	Ports comply with IEEE 802.3at/af standards
PoE Priority	Intelligent Power Management: Automatically disconnect the last powered device when power exceeds budget
Shielded RJ45 Port	True
Extend Mode Ports	#9~#16
VLAN Mode Ports	#1~#16
LED	Power, PoE Status of each PoE Port, Link/ACT of each Ethernet Port, PoE Max Status
Power Interfaces	AC Inlet
Physical Buttons	Extend On/Off, VLAN On/Off, PoE Watchdog On/Off
Physical Buttons Note	PoE Watchdog reboots inactive clients for 5 minutes; avoid if clients have online auto-upgrade
Copper Speed & Distance	Cat.3+: 100 m @ 10 MbpsCat.5+: 100 m @ 100 MbpsCat.5e+: 100 m @ GigabitCat.5e+: 250 m @ 10 Mbps

Copper Speed Note	250 m transmission only available on Extend Mode ports when activated
Optical Spec & Distance	Depends on installed optical module
MAC Address Table	8192
Max Switching Capacity	36 Gbps
Max Forwarding Rate	26.78 Mpps
Jumbo Frame	15 KB
Packet Buffer	4 Mbit
Power Methods	AC
Power Input	100-240V~ 50/60Hz
Power Supply	200W
Max Power Excluding PoE	14W
Switching Protocols	802.3i, 802.3u, 802.3ab, 802.3z, 802.3x Flow Control, 802.3af PoE, 802.3at PoE
PoE Management	Intelligent Power Management
L2 Features	Loop Prevention, Loop Detection, DSCP QoS, 802.1p QoS
Grounding Methods	Three-Prong Plug
EMS	IEC/EN 61000-4-2 Level 3 ESD: Contact 6kV, Air 8kVIEC/EN 61000-4-5 Level 4 Surge: Power DM 2kV, CM 4kV; RJ45 CM 6kV
Operating Temperature	0~40 °C (32~104 °F)
Storage Temperature	-40~70 °C (-40~158 °F)
Operating Humidity	10~90% non-condensing
Storage Humidity	10~95% non-condensing
Dimensions	440×220×44 mm (17.32×8.66×1.73 in)
Product Weight	2773.5 g (97.83 oz.)
Casing Material	Metal
Installation	Desktop, Rackmount via Brackets
Package Content	GS1020PS2, Power Cord, Mounting Kit, Installation Guide

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.