

Kategorija: **Intel matične ploče**

Proizvođač: **Gigabyte**

Matična ploča 1700 Gigabyte H610I DDR5

2xDP/HDMI/VGA/M.2

Maloprodajna cena: 18.990,00 RSD

Web cena: 18.990,00 RSD

Šifra: **H610I DDR5**



Specifikacija

| | |
|-------------------------------------|---|
| Model | Gigabyte H610I DDR5 LGA1700 Mini ITX Matična ploča |
| Socket | Intel Socket 1700 (LGA1700) |
| Skup čipova (Chipset) | Intel H610 |
| Podrška za procesore | Support for the 14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron |
| Tip memorije (RAM) | DDR5 |
| Broj memorijskih slotova | 2x 288-Pin DDR5 |
| Podrška za memorije | 13th Generation Intel Core i9/i7 Processors:- Support for DDR5 5600/5200/4800/4400 MT/s memory modules13th Generation Intel Core i5/i3 and 12th Generation Intel Core, Pentium Gold and Celeron Processors:- Support for DDR5 4800/4400 MT/s memory module2 x DDR DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules |
| Podrška za grafiku - portovi | Integrated Graphics Processor-Intel HD Graphics support:- 1 x D-Sub port, supporting a maximum resolution of 1920x1200 60Hz- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60HzSupport for DisplayPort 1.2 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz |
| Slotovi za proširenja | 1 x PCI Express x16 slot, running at x16(The PCIEX16 slot conforms to PCI Express 4.0 standard.) |
| M.2 portovi | 1x M.2 Socket 3 |
| Čuvanje podataka - portovi | Chipset:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 3.0 x4/x2 SSD support)- 4 x SATA 6Gb/s connectors |
| SATA portovi | 4x SATA 6Gb/s |
| LAN | Intel GbE LAN chip (1 Gbps/100 Mbps) |
| Zvuk (Audio) | Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channel |

| | |
|------------------------------------|---|
| USB portovi | Chipset:- 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)- 4 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub:- 2 x USB 2.0/1.1 ports available through the internal USB header |
| Konektori na zadnjoj strani | 1 x PS/2 keyboard/mouse port 2 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x D-Sub port 2 x DisplayPorts 1 x HDMI port 1 x RJ-45 port 3 x audio jacks |
| Unutrašnji konektori | 1 x 24-pin ATX main power connector 1 x 4-pin ATX 12V power connector 1 x CPU fan header 1 x system fan header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) 1 x serial port header 1 x Clear CMOS jumper 1 x chassis intrusion header |
| Posebne mogućnosti | Support for APP Center- BIOS- EasyTune- Ambient LED- Smart Backup- System Information Viewer Support for Q-Flash Support for Xpress Install Voltage detection Temperature detection Fan speed detection Fan fail warning Fan speed control Norton Internet Security (OEM version) LAN bandwidth management software |
| Operativni sistem | Windows 10; Windows 11 |
| BIOS | 1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 |
| Format | Mini-ITX |

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.