Kategorija: **Intel matične ploče**
Proizvođač: **Gigabyte**

Šifra: **H610I DDR5**

Matična ploča 1700 Gigabyte H610I DDR5 2xDP/HDMI/VGA/M.2

Web cena: 18.990,00 RSD



Specifikacija

Model	Gigabyte H610I DDR5 LGA1700 Mini ITX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel H610
Podrška za procesore	Support for the 14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	2x 288-Pin DDR5
Podrška za memorije	13th Generation Intel Core i9/i7 Processors:- Support for DDR5 5600/5200/4800/4400 MT/s memory modules13th Generation Intel Core i5/i3 and 12th Generation Intel Core, Pentium Gold and Celeron Processors:- Support for DDR5 4800/4400 MT/s memory module2 x DDR DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support:- 1 x D-Sub port, supporting a maximum resolution of 1920x1200 60Hz- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60HzSupport for DisplayPort 1.2 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
Slotovi za proširenja	1 x PCI Express x16 slot, running at x16(The PCIEX16 slot conforms to PCI Express 4.0 standard.)
M.2 portovi	1x M.2 Socket 3
Čuvanje podataka - portovi	Chipset:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 3.0 x4/x2 SSD support)- 4 x SATA 6Gb/s connectors
SATA portovi	4x SATA 6Gb/s
LAN	Intel GbE LAN chip (1 Gbps/100 Mbps)
Zvuk (Audio)	Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channel

USB portovi	**Chipset:**- 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)- 4 x USB 2.0/1.1 ports on the back panel**Chipset+USB 2.0 Hub:**- 2 x USB 2.0/1.1 ports available through the internal USB header
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port2 x USB 3.2 Gen 1 ports4 x USB 2.0/1.1 ports1 x D-Sub port2 x DisplayPorts1 x HDMI port1 x RJ-45 port3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector1 x 4-pin ATX 12V power connector1 x CPU fan header1 x system fan header1 x RGB LED strip header1 x M.2 Socket 3 connector4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x speaker header1 x USB 3.2 Gen 1 header1 x USB 2.0/1.1 header1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)1 x serial port header1 x Clear CMOS jumper1 x chassis intrusion header
Posebne mogućnosti	Support for APP Center- BIOS- EasyTune- Ambient LED- Smart Backup- System Information ViewerSupport for Q-FlashSupport for Xpress InstallVoltage detectionTemperature detectionFan speed detectionFan fail warningFan speed controlNorton Internet Security (OEM version)LAN bandwidth management software
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Mini-ITX

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što prezicniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.