

Kategorija: **Intel matične ploče**

Proizvođač: **Gigabyte**

Matična ploča 1700 Gigabyte B760M G XWF6E GEN5

Maloprodajna cena: 14.990,00 RSD

Web cena: 14.990,00 RSD

Šifra: **B760M G XWF6E GEN5**



Specifikacija

Model	Gigabyte B760M GAMING X WIFI6E GEN5 LGA1700 Micro ATX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel B760
Podrška za procesore	Intel Core, Pentium Gold and Celeron Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5 Support for DDR5 7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000 MT/s memory modules4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modulesSupport for Extreme Memory Profile (XMP) memory modules(The CPU and memory configuration may affect the supported memory types, data rate (speed), and number of DRAM modules, please refer to "Memory Support List" on GIGABYTE's website for more information.)
Podrška za memorije	
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel® HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60HzSupport for DisplayPort 1.2 version and HDCP 2.3
Slotovi za proširenja	CPU :- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset :- 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4)
M.2 portovi	2x M.2 Socket 3

Čuvanje podataka - portovi

SATA portovi

LAN

Bežična mreža

Bluetooth

Zvuk (Audio)

USB portovi

Konektori na zadnjoj strani

Unutrašnji konektori

Posebne mogućnosti

Operativni sistem

BIOS

Format

Link ka proizvođaču

CPU:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU)**Chipset:-** 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices

4x SATA 6Gb/s

Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

Intel Wi-Fi 6E AX210- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands

5.3

Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channelYou can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.Support for S/PDIF Out

Chipset:- 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header- 5 x USB 3.2 Gen 1 ports (3 ports on the back panel, 2 ports available through the internal USB header)- 1 x USB 2.0/1.1 port on the back panel**Chipset+2 USB 2.0 Hubs:-** 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)

3 x USB 3.2 Gen 1 ports5 x USB 2.0/1.1 ports2 x antenna connectors (2T2R)1 x HDMI port (Note)1 x DisplayPort (Note)1 x RJ-45 port3 x audio jacks

1 x 24-pin ATX main power connector1 x 8-pin ATX 12V power connector1 x CPU fan header3 x system fan headers3 x addressable LED strip headers1 x RGB LED strip header2 x M.2 Socket 3 connectors4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x S/PDIF Out header1 x USB Type-C header, with USB 3.2 Gen 2 support1 x USB 3.2 Gen 1 header2 x USB 2.0/1.1 headers2 x Thunderbolt add-in card connectors1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)1 x serial port header1 x Q-Flash Plus button1 x reset jumper1 x Clear CMOS jumper

Support for GIGABYTE Control Center (GCC)Support for Q-FlashSupport for Q-Flash PlusSupport for Smart Backup

Windows 10; Windows 11

1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Micro ATX

<https://www.gigabyte.com/>

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.