

Kategorija: **AMD matične ploče**Proizvođač: **Gigabyte**Šifra: **4719331806422**

Matična ploča AM4 Gigabyte X570 GAMING X

Matična ploča AM4 Gigabyte X570 GAMING X**Maloprodajna cena: 23.890,00 RSD****Web cena: 22.890,00 RSD****Ušteda: 1.000,00 RSD**

Specifikacija

Tip procesora	AMD
Podnožje	AMD® AM4
Čipset	AMD® X570
Format ploče	ATX
Podržani procesori	AMD Socket AM4, support for: 3rd Generation AMD Ryzen™ processors/ 2nd Generation AMD Ryzen™ processors/ 2nd Generation AMD Ryzen™ with Radeon™ Vega Graphics processors/ AMD Ryzen™ with Radeon™ Vega Graphics processors
Podržana memorija	DDR4 3rd Generation AMD Ryzen™ processors: Support for DDR4 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memory modules 2nd Generation AMD Ryzen™ processors/2nd Generation AMD Ryzen™ with Radeon™ Vega Graphics processors/AMD Ryzen™ with Radeon™ Vega Graphics processors: Support for DDR4 3200(O.C.) / 2933 / 2667 / 2400 / 2133 MHz memory modules 4 x DDR4 DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules*
Memorija	* ECC mode supported by 3rd Gen AMD Ryzen™ / 2nd Gen AMD Ryzen™ and only PRO sku of 2nd Gen AMD Ryzen™ with Radeon™ Vega Graphics processors/ AMD Ryzen™ with Radeon™ Vega Graphics processors. Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Multi-GPU podrška	Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™ technologies * For 3rd Generation AMD Ryzen™ processors/2nd Generation AMD Ryzen™ processors only.
Integrirana grafička karta	Integrated Graphics Processor: 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.0 version, HDCP 2.2, and HDR. Maximum shared memory of 16 GB Note: For 2nd Generation AMD Ryzen™ with Radeon™ Vega Graphics processors/AMD Ryzen™ with Radeon™ Vega Graphics processors only.

Slotovi za proširenje	Integrated in the CPU (PCIEX16): · 3rd Generation AMD Ryzen™ processors: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 · 2nd Generation AMD Ryzen™ processors: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16 * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot. · 2nd Generation AMD Ryzen™ with Radeon™ Vega Graphics processors/AMD Ryzen™ with Radeon™ Vega Graphics processors: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x8 Integrated in the Chipset (PCIEX4/PCIEX1) 1 x PCI Express x16 slot, supporting PCIe 4.0*/3.0 and running at x4 (PCIEX4) * For 3rd Generation AMD Ryzen™ processors only. 3 x PCI Express x1 slots, supporting PCIe 4.0*/3.0 * For 3rd Generation AMD Ryzen™ processors only. Integrated in the CPU (M2A_SOCKET): · 3rd Generation AMD Ryzen™ processors: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280/22110 SATA and PCIe 4.0 x4/x2 SSD support) · 2nd Generation AMD Ryzen™ processors/2nd Generation AMD Ryzen™ with Radeon™ Vega Graphics processors/AMD Ryzen™ with Radeon™ Vega Graphics processors: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280/22110 SATA and PCIe 3.0 x4/x2 SSD support) Integrated in the Chipset (M2B_SOCKET): 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280/22110 SATA and PCIe 4.0*/3.0 x4/x2 SSD support) * For 3rd Generation AMD Ryzen™ processors only. 6 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, and RAID 10
Storage	Realtek® GbE LAN chip (10/100/1000 Mbit) Realtek® ALC887 codec High Definition Audio 2/4/5.1-channel
Mrežna karta	Integrated in the CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 4 x
Zvučna karta	USB 3.2 Gen 1 ports available through the internal USB headers 6 x USB
USB	2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x PS/2 keyboard port 1 x PS/2 mouse port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x water cooling CPU fan header 2 x system fan headers 1 x CPU cooler LED strip/RGB LED strip header 2 x addressable LED strip headers 2 x RGB LED strip headers 6 x SATA 6Gb/s connectors 2 x M.2 Socket 3 connectors 1 x front panel header 1 x front panel audio header 2 x USB 3.2 Gen 1 headers 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x Clear CMOS jumper 1 x Q-Flash Plus button
Interni konektori	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Bios	Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS AutoGreen Cloud Station EasyTune Fast Boot Game Boost ON/OFF Charge RGB Fusion Smart Backup Smart Keyboard Smart Survey System Information Viewer USB Blocker Support for Q-Flash Plus Support for Q-Flash Support for Xpress Install
Ostalo	

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.